



RF 463 704

fully integrated
Width 24" (61 cm)
Right-hinged

RF 463 705

fully integrated
Width 24" (61 cm)
Left-hinged

Included accessories

Accessory for side-by-side installation
1 supply hose, 47" (1.2 m) with
 $\frac{7}{16}$ " – 24 male connector

Installation accessories

RA 422 611

Stainless steel door panel with handle
For RF 463, panel thickness $\frac{3}{4}$ ".

RA 423 140

Side trims, long.

RA 425 110

Long stainless steel handle, length
44 $\frac{1}{2}$ ", with three brackets, drilling
distance between each mount 21 $\frac{13}{16}$ ".

RA 428 811

Stainless steel door panel, **handleless**
For RF 463, panel thickness $\frac{3}{4}$ ".

RA 460 013

Additional side heating element 110 V.
Required if appliances are installed
handle to hinge or hinge to hinge.
Not required if appliances are installed
less than 6" (160 mm) apart from
each other.

RA 460 020

Connecting element for vertically split
appliance fronts (for a flush front).

RA 464 613

Ventilation grill stainless steel
For RF 463, with filter, right-hinged.

RA 464 614

Ventilation grill stainless steel
For RF 463, with filter, left-hinged.

Optional accessories

RA 450 000

Mechanical particle filter.

RA 450 010

Activated charcoal filter for water filter
system including saturation indicator.

400 series freezer column

RF 463

- Stainless steel interior with solid anthracite aluminum elements
- Warm white and glare-free LED light spots
- Net volume 11.2 cu.ft.
- Opening assist for door with two options:
 1. Push-to-open function for integration into handleless furniture front
 2. Pull-to-open function to facilitate opening the door using a handle
- The drawers in the RC and RF models are positioned at the same height. With side-by-side installation, the glass shelves and door racks can be aligned on the same level
- Material and aesthetics of interior as for RC model
 - Glass shelves
 - Solid anthracite aluminum door racks
- Flat stainless steel inner door, full-length
- Almost invisible rail system for shelves and door racks for flexible positioning
- Ice and water dispenser in the door
- Integrated ice maker with fixed inlet water connection
- Proximity sensor for ice and water dispenser
- Illuminated dispenser for ice cubes, crushed ice and chilled water
- TFT touch display
- ENERGY STAR® certified
- Sabbath mode certified by Star-K

Operation

TFT touch display operation.
Clear text display.
Touch key operation for ice and water dispenser.

Features

Dynamic cold air distribution.
Automatic defrosting with defrost water evaporation.
Sabbath mode certified by Star-K. When sabbath mode is active, the appliance can only be opened using a handle.
Open-door and malfunction alarm.
Home network integration for digital services (Home Connect) wireless via WiFi.
For further information please check: home-connect.com.

Freezing

No-frost technology with fast freezing at -22°F (-30°C).
Temperature adjustable from 3°F to -11°F (-16°C to -24°C).
4 safety glass shelves, white glass, 2 of which are individually adjustable in height.
2 fully extendable drawers with transparent front.
4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.
Net volume 11.2 cu.ft.

Ice and water dispenser

Warm white LED lighting.
Proximity sensor for automatic

activation of light and touch keys for ice and water dispenser.
Integrated, with fixed inlet water connection.
Particle filter for water inlet, integrated in ventilation grill area.
Can be switched off.
Ice cube production approx. 4.2 lbs. (1.9 kg)/24 h.
Ice cubes and crushed ice.
Removable ice storage container with approx. 6.6 lbs. (3 kg) capacity.
Ice water supply approx. .05 cu.ft. (1.5 liters).

Consumption data

Energy consumption
457 kWh/year.
Noise level 42 dBA.

Planning notes

Flat hinge.
Door opening angle of 115°, fixable at 90°.
Max. door panel weight 147 lbs. (67 kg).
Shut-off valve for water connection must be planned next to the appliance and always be accessible.
If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

Rating

Total rating 1.252 kW/24h.
Total Amps: 15 A.
120 V / 60 Hz
Connecting cable 118" (3m), detachable.
Water inlet.
Supply hose 47" (1.2 m) with $\frac{7}{16}$ " – 24 male connector.
Water pressure 29 to 116 psi.



