Specifications

Video Display System NTSC/PAL Compatibility

DISPLAY SCREEN

10.1"
221mm (8.70")
132mm (5.20")
16:9
Liquid Crystal Display
TFT-LCD, Active Matrix
1024(W) x 600(H) x 3
1.84M Pixels (WSVGA)
99.9% or more
LED
10 – 16 V DC

	(Typical: 12V)
Power Consumption	2.35A (MAX)
	1.60A (TYP)
	140mA (Stand by)
Video Input	1.0V p-p 750hm
Audio Input	2.0V rms (max)
IR Transmitter	CH A: 2.3MHz / 2.8MHz
	CH B: 3.2 MHz / 3.8MHz
FM Modulator	88.1MHz - 92.1MHz
	PLL Frequency
	Synthesizer
Operating Temperature	14 °F to +158 °F (-10 °C
	to + 70 °C)

MONITOR

Width	290 mm (11.42")
Depth	290 mm (11.42")
Height (LCD Panel Closed)	45 mm (1.7")
Height (LCD Panel Open)	204.2 mm (8.04")
Weight	2.270 Kg (5.0lbs)

DOLBY.

Manufactured under license from Dolby Laboratories. Dolby and the double-D symbol are trademarks of Dolby Laboratories.

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and other countries.

This product incorporates copyright protection technology that is protected by U.S. patents and other intellectual property rights. Use of this copyright protection technology must be authorized by Rovi Corporation, and is intended for home and other limited viewing uses only unless otherwise authorized by Rovi Corporation. Reverse engineering and disassembly are prohibited.