

AT8033

Cardioid Condenser Microphone



Features

- **All-purpose condenser microphone ideal for audio acquisition in the studio and on stage; use for interviews, acoustic guitar, percussion, overheads, group vocals and more**
- **Low-mass diaphragm ensures minimum distortion**
- **High SPL capability and wide frequency response**
- **Cardioid polar pattern reduces pickup of sounds from the sides and rear, improving isolation of desired sound source**
- **Switchable 80 Hz high-pass filter minimizes pickup of undesired low-frequency sounds**
- **Offers the convenience of battery or phantom power operation**

Description

The AT8033 is an all-purpose condenser microphone ideal for general audio acquisition including interviews, acoustic guitar, percussion, overheads, vocals and more.

The microphone requires 11V to 52V phantom power or a 1.5V AA battery for operation. A battery need not be in place for phantom power operation.

The cardioid polar pattern of the microphone is more sensitive to sound originating directly in front of the element, making it useful for controlling feedback and reducing pickup of unwanted sounds.

The output of the microphone is a 3-pin XLRM-type connector.

A switch permits choice of flat response or low-frequency roll-off (via integral 80 Hz high-pass filter) to help control undesired ambient noise.

The microphone is enclosed in a rugged housing. The included AT8405a stand clamp permits mounting on any microphone stand with $\frac{5}{8}$ "-27 threads. A windscreen, a battery and a soft protective pouch are also included.

Operation and Maintenance

The AT8033 requires 11V to 52V phantom power or a 1.5V AA battery for operation. A battery need not be in place for phantom power operation.

To install the battery, unscrew the lower section of the microphone body, just below the nameplate. Insert a fresh 1.5V AA battery in the handle compartment ("+" end up), then reassemble the microphone. For longest battery life, the switch should remain off except when the

microphone is in use. Alkaline batteries are recommended for longest life. Remove the battery during long-term storage.

Output is low impedance (Lo-Z) balanced. The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot"—positive acoustic pressure produces positive voltage at Pin 2.

To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc.

An integral 80 Hz high-pass filter provides easy switching from a flat frequency response to a low-end roll-off. The roll-off position reduces the pickup of low-frequency ambient noise (such as traffic, air-handling systems, etc.), room reverberation and mechanically coupled vibrations. To engage the high-pass filter, slide the switch toward the "bent" line.

The high sensitivity of the microphone assures useful output and an excellent match to most input sources. In some cases, however, an attenuator may be required between the microphone and preamplifier to avoid overloading sensitive input stages.

Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for extended periods. Extremely high humidity should also be avoided.

Architect's and Engineer's Specifications

The microphone shall be a fixed-charge condenser designed for general audio acquisition. It shall have a cardioid polar pattern with a uniform 120° angle of acceptance and a frequency response of 30 Hz to 20,000 Hz. The microphone shall operate from an external 11V to 52V DC phantom power source, or alternatively, from a 1.5V AA/UM3 battery. It shall be capable of handling sound input levels up to 137 dB (phantom) or 123 dB (battery) with a dynamic range of 113 dB (phantom) or 99 dB (battery). Nominal open-circuit output voltage shall be 6.3 mV (phantom) or 5.6 mV (battery) at 1V, 1 Pascal. Output shall be low impedance balanced (250 ohms – phantom, 300 ohms – battery).

The output of the microphone shall be a 3-pin XLRM-type connector.

The microphone shall include a switch that permits choice of flat response or 80 Hz low-frequency roll-off.

The microphone shall be 194.2 mm (7.65") long and have a head diameter of 26.0 mm (1.02"). Weight shall be 159 grams (5.6 oz). The microphone shall include a stand clamp, a windscreen, a battery and a soft protective pouch.

The Audio-Technica AT8033 is specified.

Specifications

| | |
|--|---|
| Element | Fixed-charge back plate, permanently polarized condenser |
| Polar pattern | Cardioid |
| Frequency response | 30-20,000 Hz |
| Low frequency roll-off | 80 Hz, 18 dB/octave |
| Open circuit sensitivity | Phantom: -44 dB (6.3 mV) re 1V at 1 Pa Battery: -45 dB (5.6 mV) re 1V at 1 Pa |
| Impedance | Phantom: 250 ohms Battery: 300 ohms |
| Maximum input sound level | Phantom: 137 dB SPL, 1 kHz at 1% T.H.D. Battery: 123 dB SPL, 1 kHz at 1% T.H.D. |
| Dynamic range (typical) | Phantom: 113 dB, 1 kHz at Max SPL Battery: 99 dB, 1 kHz at Max SPL |
| Signal-to-noise ratio¹ | 70 dB, 1 kHz at 1 Pa |
| Phantom power requirements | 11-52V DC, 2 mA typical |
| Battery type | 1.5V AA/UM3 |
| Battery current / life | 0.4 mA / 1200 hours typical (alkaline) |
| Switch | Flat, roll-off |
| Weight | 159 g (5.6 oz) |
| Dimensions | 194.2 mm (7.65") long, 26.0 mm (1.02") head diameter |
| Output connector | Integral 3-pin XLRM-type |
| Audio-Technica case style | S4 |
| Accessories furnished | AT8405a stand clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter; AT8136 windscreen; battery; soft protective pouch |

In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.


1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

¹ Typical, A-weighted, using Audio Precision System One.


Specifications are subject to change without notice.



frequency response: 30–20,000 Hz



polar pattern



 **audio-technica**

Audio-Technica Corporation
audio-technica.com ©2016 Audio-Technica

0001-0177-02