

Specifications

Frequency Response	20-27,000 Hz
Channel Separation	28 dB (1 kHz)
Vertical Tracking Force	1.8-2.2 g (2.0 g standard)
Stylus Construction	Nude square shank
Recommended Load Impedance	47,000 ohms
Output	4.0 mV (at 1 kHz, 5 cm/sec)
Channel Balance	1.0 dB (1 kHz)
Stylus Shape	2.2 x 0.12 mil MicroLine®
Cantilever	Aluminum tapered pipe
Mount	Half-inch
Replacement Stylus	VMN40ML

Coil Impedance: 2,700 ohms (1 kHz)

DC Resistance: 800 ohms

Load Capacitance: 100-200 pF

Coil Inductance: 460 mH (1 kHz)

Static Compliance: 40×10^{-6} cm/dyne

Dynamic Compliance: 10×10^{-6} cm/dyne (100 Hz)

Vertical Tracking Angle: 23°

Dimensions (Cartridge): 17.3 mm (0.7") H x 17.0 mm (0.7") W x 28.2 mm (1.1") D

Weight (Cartridge): 6.4 g (0.2 oz)

Dimensions (Cartridge & Headshell): 21.3 mm (0.8") H x 21.0 mm (0.8") W x 60.4 mm (2.4") D

Weight (Cartridge & Headshell): 16.8 g (0.6 oz)

Accessories Included: Four cartridge installation screws (5 mm x 2, 10 mm x 2), two washers, two hexagon nuts, non-magnetic screwdriver, brush, lead wire set