

## Specifications

|                            |                             |
|----------------------------|-----------------------------|
| Frequency Response         | 20-27,000 Hz                |
| Channel Separation         | 28 dB (1 kHz)               |
| Vertical Tracking Force    | 1.8-2.2 g (2.0 g standard)  |
| Stylus Construction        | Nude square shank           |
| Recommended Load Impedance | 47,000 ohms                 |
| Output                     | 4.0 mV (at 1 kHz, 5 cm/sec) |
| Channel Balance            | 1.0 dB (1 kHz)              |
| Stylus Shape               | 2.2 x 0.12 mil MicroLine®   |
| Cantilever                 | Aluminum tapered pipe       |
| Mount                      | Half-inch                   |
| Replacement Stylus         | VMN40ML                     |

---

**Coil Impedance:** 2,700 ohms (1 kHz)

**DC Resistance:** 800 ohms

**Load Capacitance:** 100-200 pF

**Coil Inductance:** 460 mH (1 kHz)

**Static Compliance:** 40 x 10<sup>-6</sup> cm/dyne

**Dynamic Compliance:** 10 x 10<sup>-6</sup> cm/dyne (100 Hz)

**Vertical Tracking Angle:** 23° Dimensions: 17.3 mm (0.7") H x 17.0 mm (0.7") W x 28.2 mm (1.1") D

**Weight:** 6.4 g (0.2 oz)

**Accessories Included:** Four cartridge installation screws (5 mm x 2, 10 mm x 2), two washers, two hexagon nuts, non-magnetic screwdriver, brush, lead wire set