

Specifications

Frequency Response	20-30,000 Hz
Channel Separation	30 dB (1 kHz)
Vertical Tracking Force	1.8-2.2 g (2.0 g standard)
Stylus Construction	Nude rectangular shank
Recommended Load Impedance	47,000 ohms
Output	4.0 mV (at 1 kHz, 5 cm/sec)
Channel Balance	1.0 dB (1 kHz)
Stylus Shape	1.5 x 0.28 mil special line contact
Cantilever	Aluminum tapered pipe
Mount	Half-inch
Replacement Stylus	VMN60SLC

Coil Impedance: 2,700 ohms (1 kHz)

DC Resistance: 800 ohms

Load Capacitance: 100-200 pF

Coil Inductance: 460 mH (1 kHz)

Static Compliance: 40×10^{-6} cm/dyne

Dynamic Compliance: 10×10^{-6} cm/dyne (100 Hz)

Vertical Tracking Angle: 23°

Dimensions: 17.3 mm (0.7") H x 17.0 mm (0.7") W x 28.2 mm (1.1") D

Weight: 8.0 g (0.3 oz)

Accessories Included: Four cartridge installation screws (5 mm x 2, 10 mm x 2), two washers, two hexagon nuts, non-magnetic screwdriver, brush, lead wire set