

HD-RX1-F

HDMI® over Fiber Receiver

- > Extends uncompressed digital video, audio, and control signals 1000 feet (300 m) over a single multimode fiber
- > Works reliably without any programming or configuration
- > Supports HDMI® with Deep Color
- > Also compatible with DVI^[3]
- > Supports 7.1 channel lossless audio up to 48 kHz
- > Supports DTS® and Dolby Digital® encoded audio
- > Handles resolutions up to WUXGA 1920x1200 and HD 1080p60
- > Passes CEC, EDID, and HDCP
- > Includes universal IR repeater up to 192 kHz
- > Extends bidirectional RS-232 up to 115k Baud
- > Provides electrical isolation for outdoor runs
- > 12VDC universal power pack included



Crestron® HDMI® over Fiber Transmitters and Receivers deliver professional-grade digital HD AV signal extension for use in the home, classroom, auditorium, or corporate boardroom. Without any special setup or configuration, the HD-RX1-F receiver works with an [HD-TX1-F](#) transmitter^[1] to enable wire runs up to 1000 feet (300 m) over a single multimode fiber strand^[2]. The use of fiber not only facilitates long wire runs, but is also ideal for wiring to outdoor devices and between buildings, providing optical isolation against ground loops, lightning surges, and other electrical disturbances. The HD-RX1-F simultaneously handles high-definition digital video and audio, RS-232, and IR signals.

Robust HD Signal Extension

Crestron HDMI over Fiber technology delivers ultra-reliable extension of uncompressed video and computer signals. The HD-RX1-F handles video resolutions up to Full HD 1080p60, and computer resolutions up to UXGA and WUXGA, with support for HDCP and Deep Color. Audio capabilities include support for Dolby Digital®, DTS®, and uncompressed 7.1 linear PCM. In addition to HDMI, the HD-RX1-F is also compatible with DVI display devices using an appropriate adapter or interface cable^[3].

...And Control Too!

In addition to video and audio, the HD-RX1-F provides for the extension of control signals for a true one-wire AV interface solution. Both IR and bidirectional RS-232 control signals may be routed to control a display device or other equipment.

Comprehensive without Complication

Crestron HDMI over Fiber affords a very dependable signal extension solution that's simple to implement. No special configuration or programming is required — just connect your source and display and enjoy high-quality HD video and audio from across the room — or from another entire building. The HD-RX1-F is housed in an attractive, compact enclosure, with provisions for mounting to any flat surface, or to one rail of a 19" EIA equipment rack.

Crestron offers the fiber optic cable, connectors, and termination kit for a complete, easy wiring solution. A range of professional AV interface cables and wall plates is also available to complement the HD-RX1-F for a total custom installation solution.^[1]

HD-RX1-F HDMI® over Fiber Receiver



Bottom Panel View



Top Panel View

SPECIFICATIONS

Video

Output Signal Types: HDMI® w/Deep Color (DVI compatible^[3])
Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165 MHz pixel clock
Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165 MHz pixel clock

Audio

Output Signal Types: HDMI
Formats: Dolby Digital®, Dolby Digital EX, DTS®, DTS-ES, DTS 96/24, LPCM up to 8 channels
Sampling Rate: Up to 48 kHz

Communications

Fiber: 50/125 or 62.5/125 µm multimode optical fiber, 1000 ft (300 m) cable length, 850 nm & 1310 nm transmit, 1550 nm receive^[2]

Connectors

IR: (1) 2-pin 3.5 mm detachable terminal block;
IR/Serial repeater output port;
IR output up to 192 kHz;
1-way serial TTL/RS-232 (0-5 Volts) up to 19200 baud

HDMI OUT: (1) 19-pin Type A HDMI female;
HDMI digital video/audio output (DVI compatible^[3])

COM: (1) 3-pin 3.5 mm detachable terminal block;
Bidirectional RS-232 port;
Up to 115.2k baud, software handshaking support

G: (1) 6-32 screw, chassis ground lug

MM OPTICAL: (1) SC female optical fiber connector;
Multimode fiber input;
Connects to MM OPTICAL port of an HD-TX1-F transmitter via CresFiber 8G fiber optic cable^[2]

12VDC 0.5A: (1) 2.5 x 5.5 mm DC power connector;
12 Volt DC power input;
PW-1205RU power pack included

Note: Mini USB port is for factory use only.

Indicators

Power: (1) Green LED, indicates operating power supplied via external power pack

Power Requirements

Power Pack: 0.5 Amps @ 12 Volts DC;
100-240 Volts AC, 50/60 Hz power pack, model PW-1205RU, included

HD-RX1-F HDMI® over Fiber Receiver

Environmental

Temperature: 32° to 104° F (0° to 40° C)

Humidity: 10% to 90% RH (non-condensing)

Enclosure

Chassis: Aluminum w/polycarbonate label overlay and (4) integral mounting flanges

Mounting: Freestanding, surface mount, or attach to a single rack rail

Dimensions

Height: 5.92 in (150 mm)

Width: 3.91 in (100 mm)

Depth: 1.43 in (37 mm)

Weight

14.7 oz (416 g)

MODELS & ACCESSORIES

Available Models

HD-RX1-F: HDMI® over Fiber Receiver

Included Accessories

PW-1205RU: Wall Mount Power Pack, 12VDC, 0.5A, 2.5mm, Universal (Qty. 1 included)

Available Accessories

HD-TX1-F: HDMI® over Fiber Transmitter

IRP2: IR Emitter Probe

CNSP-XX: Custom Serial Interface Cable

CRESFIBER-SINGLE-SC-P: CresFiber® Simplex Fiber Optic Cable Assembly, 50/125, SC, Plenum

CRESFIBER8G-NP: CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, non-plenum

CRESFIBER8G-P: CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, plenum

CRESFIBER-CONN-SC50UM-12: Connectors for CresFiber® 8G Multimode Fiber Optic Cable, SC 50µm, 12-Pack

CRESFIBER-TK: CresFiber® Termination Kit

CBL Series: Crestron® Certified Interface Cables

MP-WP Series: Media Presentation Wall Plates

MPI-WP Series: Media Presentation Wall Plates - International Version

Notes:

1. Item(s) sold separately.
2. For MM OPTICAL fiber wiring, use [CresFiber 8G](#) or other quality 50/125 or 62.5/125 µm multimode fiber optic cable. To achieve maximum distance, the cable should be rated for at least 500 MHz*km effective modal bandwidth (EMB) at both 850 nm and 1300 nm.
3. HDMI requires an appropriate adapter or interface cable to accommodate a DVI signal. [CBL-HD-DVI](#) interface cables are available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and CresFiber are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby Digital is either a trademark or registered trademark of Dolby Laboratories in the United States and/or other countries. DTS is either a trademark or registered trademark of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.

HD-RX1-F HDMI® over Fiber Receiver

