

## 6.5" 2-Way Surface Mount Media Presentation Speaker

- > Compact, high-performance 2-way speaker
- > Long-throw 6.5" woofer and 1" wide-dispersion soft dome tweeter
- > Dual tuned bass reflex ports for extended bass
- > Attractive high-impact plastic housing with protective metal grille
- > Adjustable surface mount bracket included
- > 80 Watts power handling
- > 56 Hz to 20 kHz frequency response
- > Available in white or black

The Crestron® FS6 is an attractive, compact loudspeakers designed for multimedia presentation and speech reinforcement in classrooms and other indoor applications. It features a 6.5" long-throw woofer delivering extended bass response through a dual tuned bass reflex design. High frequencies are crisp and smooth thanks to the 1" wide-dispersion soft dome tweeter. Careful design of the enclosure and crossover assures natural, detailed midrange to cut through the noise of a classroom environment.

A pair of FS6 speakers provides exceptional sonic performance and wide coverage for a typical classroom, and a second pair may be employed to cover larger rooms. Each speaker boasts power handling up to 80 Watts, and may be used with any amplifier from 5 to 120 Watts. Clean, versatile mounting is provided via adjustable "C" brackets, which may be oriented horizontally or vertically.

FS6 speakers are available in white or black. They are priced individually, but must be ordered in pairs.

### SPECIFICATIONS

#### Features & Performance

**Woofer:** 6.5 inch (165 mm) long-throw with dual tuned bass reflex ports

**Tweeter:** 1 inch (25 mm) wide dispersion soft dome

**Impedance:** 8 Ohms nominal

**Frequency Response:** 56 Hz to 20 kHz (-10 dB)

**Power Handling:** 80 Watts maximum

**Recommended Amplifier Power:** 5 to 120 Watts

#### Environmental

**Temperature:** 41° to 104°F (5° to 40°C)

**Humidity:** 10% to 90% RH (non-condensing)

For indoor use only

#### Enclosure

**Chassis:** Contoured high-impact plastic with painted metal grille

**Mounting:** Surface mount (adjustable "C" bracket included)



#### Dimensions

**Height:** 12.57 in (320 mm) including bracket

**Width:** 8.24 in (209 mm)

**Depth:** 9.45 in (241 mm)

Dimensions shown are with bracket attached, positioned vertically and adjusted to 0° azimuth

#### Weight

6.8 lb (3.0 kg) including bracket

### MODELS & ACCESSORIES

#### Available Models

**FS6-B-T-EACH:** 6.5" 2-Way Surface Mount Media Presentation Speaker, Black Textured, Single (must be ordered in multiples of 2)

**FS6-W-EACH:** 6.5" 2-Way Surface Mount Media Presentation Speaker, White, Single (must be ordered in multiples of 2)

#### Available Accessories

**CBL-SPK-P-35:** Speaker Cable, 16AWG, Plenum, 35 ft

# FS6 6.5” 2-Way Surface Mount Media Presentation Speaker

## Notes:

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2013 Crestron Electronics, Inc.