

Color Variants DF481763 Fully integrated Appliance height 34 1/8"(86.7 cm)

Included accessories

1 x baking tray spray head. 1 x glass holder rack. 1 x GN container insert.

Optional accessories DA042030 Sterling silver cutlery cassette DA043000 Holder for long-stemmed glasses

Installation Accessories DA020110 Stainless steel trim kit for tall tub dishwashers DA021000 Folding hinge GZ010011 Extension for inlet and outlet (78" long) DF481763 400 series dishwasher

Fully integrated Appliance height 34 1/8"(86.7 cm)

Optimal drying with zeolite 8 programs with agua sensor and 5 options, such as Power and Intensive Flexible rack system with smooth running rails on all levels and a softclosing system of the upper and lower racks. TFT display for intuitive handling of all functions Remaining time projection onto the kitchen floor Perfectly illuminated interior Push-to-open function for perfect integration into handleless furniture fronts Very quiet: 42 dB Aqua stop Energy Star certified Operation

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water. Touch key operation. Information key with use indications. Sanitized indicator in the control panel. Time delay up to 24 hours. Visual and acoustic end of program indicator. Remaining time projection.

Technical Features Perfectly illuminated interior. Glass protection. Aqua sensor. Load sensor. Automatic detergent function. Yes Flow-Through Water Heater™ Triple filter system. Soft lock. Aqua stop Home network integration for digital services (Home Connect) wireless via WiFi. The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-

Programs

connect.com.

8 programs: Auto 150 °F - 160 °F. Auto 127 °F - 140 °F. Auto 113 °F - 122 °F. Standard Eco 113 °F - 136 °F. Wash and Dry 122 °F (1 h.). Quick Wash 113 °F (30 min.). Glass Care 122 °F. Pre-rinse. 5 options: Intensive. Power. Half Load. Hygiene. Extra Dry with Zeolite.

Features

Flexible rack system with smooth running rails on all levels and softclosing system of the upper and lower rack. 3rd rack for cutlery. Upper rack Over extension. Rackmatic with 3 levels, adjustable in height up to 2". 6 folding tines 4 folding racks. 2 glass support bars. Lower rack: Product Features Watts (W) 1440 Current (A) 12 Volts (V) 120 Frequency (Hz) 60 Power Cord Length 47 1/4" Minimum Water Pressure (Ib/sin) 7.0 Length inlet hose (in) 65" Length outlet hose (in)

74 3/4" Overall appliance dimensions (HxWxD) (in)

34 1/8" x 23 9/16" x 21 5/8" Required cutout size (HxWxD) (in) x 34 1/8" x 23 9/16" Adjustable feet Yes

Consumption and connection features Number of wash cycles

Number of options

Third Rack 3rd Rack 2.1

Tub material Stainless steel

Concealed heating element Yes Leak protection system 24/7 Aqua Stop Plus

Five-level wash

No Water softener No

ChildLock Yes

Total annual energy consumption (kWh) 269

Energy Efficiency Class Tier 3

Energy Star® qualified

Yes Total annual energy consumption (kWh) Total annual water consumption (g)

Number of place settings

2019-12-16 Page 1 Cutlery basket. Holder for long-stemmed glasses. Maximum dish sizes (upper/lower rack 9"/11", 8"/12", 7"/13" respectively. 13 place setting capacity. Maximum glass loading capacity 23 wine glasses.

Consumption data

Total annual energy consumption 269 kwh. From 3.5 gallons water.

Noise level 42 dB (re 1 pW).

Planning notes

Height-adjustable feet. Rear toe kick protrusion 3 15/16" (see drawing). To display the remaining time projection, a minimum plinth protrusion

is required (1 9/16" + thickness of the furniture front). The maximum plinth height must


be reduced by 1 1/16" to provide an optimal display of the remaining time projection. Rear feet adjustable at front.


Door weight up to 22 lbs for DF 481. Door panel dimension dependent on plinth height of kitchen furniture. Installation and usage also with furniture handle possible. The push-toopen function remains active.


Rating

Total rating: 1.44 kW. Connecting cable 47 1/4" with plug. Water connection with 3/4" screw joint. Connection to hot or cold water possible.











[] values with extension kit





[] values with extension kit

Measurements in inches (mm)

