



Order number: HP50609
WEEE-Reg.-Nr. DE 29323089

Downloads

> [BDA / Manual](#)

Related links

> [DSP PC-Tool V4](#)

> [Do you have any questions concerning this product?](#)

Specifications

Inputs 4 x RCA / Cinch 4 x Highlevel speaker input 1 x Optical SPDIF (12 - 96...

Inputs	4 x RCA / Cinch 4 x Highlevel speaker input 1 x Optical SPDIF (12 - 96 kHz) 1 x Remote In
Input sensitivity	RCA / Cinch 2 - 4 Volts Highlevel 5 - 11 Volts
Outputs	6 x RCA / Cinch 1 x Remote Out
Output voltage	4 Volts
Frequency response	10 Hz - 44,000 Hz
DSP resolution	64 Bit
DSP power	295 MHz (1.2 billion MAC operations/second)
Sampling rate	96 kHz

DSP type	Audio signal processor
Signal converters	A/D: Asahi Kasei D/A: Asahi Kasei
Signal-to-noise ratio digital input	106 dB (A-weighted)
Signal-to-noise ratio analog input	103 dB (A-weighted)
Total harmonic distortion (THD+N) digital input	< 0.001 %
Total harmonic distortion (THD+N) analog input	< 0.002 %
IM distortion (IMD) digital input	< 0.004 %
IM distortion (IMD) analog input	< 0.004 %
Crosstalk	> 90 dB
Operating voltage	9.6 - 18 Volts (max. 5 sec. down to 6 Volts)
Current draw	< 400 mA
Max. remote output current	500 mA
Additional features	HEC slot, Ground lift switch, Control Input, 32 Bit CoProcessor, ADEP.3 circuit, Auto Remote switch
Dimensions (H x W x D)	40 x 177 x 104 mm / 1.58 x 6.97 x 4.09"

Accessories 6



URC.3



DIRECTOR -
Display Remote



DIRECTOR
CREATE



HEC BT - DSP
MINI



HDM 2 - C FOUR



Similar products

