
KD-S4x1

4x1 4K/18G HDMI Switcher, supports HDR10, HDCP2.2

Key Features

- > Digital Switching: 4 HDMI Sources to 1 HDMI Display
- > 4K Support: 4096x2160 or 3840x2160 30Hz at 4:4:4 and 60Hz at 4:4:4
- > 18 Gbps Bandwidth: High Speed / Performance for latest HDMI standards
- > HDR10 (High Dynamic Range): More life-like images through a greater range of luminance levels
- HDCP 2.2 and HDMI Licensing: Fully licensed and compatible with HDCP 2.2 and HDMI latest technologies
- EDID Control: Internal library with 16 default EDID configurations for each input, including native EDID data of Output/Display
- > Full Buffer[™] System: Manages TMDS re-clocking / signal re-generation, HDCP source & display authentication, Hot Plug Management and EDID Control handshake
- Lossless Compressed Digital Audio: Dolby[®] TrueHD, Dolby[®] Digital Plus, Dolby[®] Atmos and DTS-HD Master Audio[™]
- > Deep Color Support: Up to 12 Bit at UHD/4K 24/25/30Hz 4:4:4
- > I2C Communication: EDID and HDCP buffering from Display to Source
- > Control: Front panel push buttons and LEDs, Optical IR
- > CEC: Full Support
- Control System Support: Fully controllable by all IR, RS-232, and TCP/IP supported control systems via open API: AMX[®], Crestron[®], KNX[®], RTI[®], Savant, URC[®], Leviton[®] etc.



Specifications

- » Input: HDMI Connector, Type A, 19 Pin Female
- » Output (Each): HDMI Connector, Type A, 19 Pin Female
- » Bandwidth: TMDS bandwidth 18 Gb/s
- » DDC Signal (Data): Input DDC Signal 5 Volts p-p (TTL)
- » HDMI Video/Audio Signal: Input Video Signal 1.2 Volts p-p
- » Power Supply: KD-PS5V1ASC, 5V/1A, 100-240VAC, 50-60Hz, Interchangeable head, screw-in connector
- » Regulation: CE, RoHS, WEEE
- » Enclosure: Black Metal
- » Product Dimensions: 6.25" x 1.1" x 3.1"
- » Packaging Dimensions: 9.8" x 4.5" x 3.35"
- » Product Weight: 0.9 lb
- » Shipping Weight: 1.5 lb



