

# **Specifications**

# **Thiele/Small Parameters**

**43CVT104** T/S Parameters PDF (/app/products/caraudio/subs/compvt16/p43cvt104/files/43CVT104.pdf)

#### SIZE [in, cm]:

10, 25

## IMPEDANCE [Ohms]:

4 SVC

## **Recommended Amplifier Power (watts RMS)**

350

## Peak Power (watts, per ANSI/CTA-2031-A)

700

## SENSITIVITY [dB 1w/1m]:

87.2

## MOUNTING DEPTH [in, cm]:

4-1/4, 10.8

#### MOUNTING DIAMETER [in, cm]:

9-3/16, 23.3

#### MIN SEALED BOX VOL [cu. ft, L]:

0.8, 22.7

## MAX SEALED BOX VOL [cu. ft, L]:

3, 85

## MIN VENTED BOX VOL [cu. ft, L]:

1.25, 35.4

## MAX VENTED BOX VOL [cu. ft, L]:

1.75, 49.6

\*Assumes typical music program with minimal amplifier clipping; varies with enclosure size. See your KICKER dealer for details.

\*\*Port Volume Excluded.

Due to continual developement, product, and specifications are subject to change without notice. Stillwater Designs and it's agents are not responsible for typographical errors.

# You may also like these related products\* -



(GR100)