

- Black Anodized Aluminum Chassis
- Top-Mounted Red LED Light Pipe

Want setup help? Go to KICKER U (/kickeru) for a woofer & amplifier configuration app!

This KX amplifier delivers as much as 400 watts into one channel. See below for more details.

Specifications

RMS Power [Watts]

@ 14.4V, 4Ω mono, ≤ 1% THD+N : 200 x 1

@ 14.4V, 2Ω mono, ≤ 1% THD+N : 400 x 1

@ 14.4V, 1Ω mono, ≤ 1% THD+N: 400 x 1 +/- 10%

Length [in, cm]

8, 20.4

Height [in, cm]

2-¹/₈, 5.5

Width [in, cm]

8-⁵/₁₆, 21

Frequency Response ± 1dB

10Hz-160Hz

Signal-to-Noise Ratio [dB]

95

Input Sensitivity

250mV-10V

Selectable Electronic Crossover

Variable Lo-pass 40Hz-160Hz, 24dB/octave

Subsonic Filter

Variable 10-80Hz, 24dB/octave

KickEQ™ Parametric Bass Boost (Remote Control Adjustable)

Boost - Variable 0-18db

Center Frequency - 20Hz-80Hz

Bandwidth 1-5

Remote Bass

Yes

CEA Power

200 x 1 @ 4 ohms, 14.4VDC, 1% THD, CEA-2006B (Watts)

CEA Signal-to-Noise Ratio

-75dB CEA-2006B (ref: 1W, A-weighted)

Support



Manuals

2017 Mono Amplifier | Multilingual | Download
(/app/manuals/amplifiers/kx/2017_KXA_Mono_Amps_Rev_H.pdf)

Do you have a different model? [Click Here \(/product-manuals\)](/product-manuals)



Support Links

Amplifier FAQ (/faq)
Extended Amplifier Warranty (/new_amp_warranty)
Wiring Diagrams (/wiring_diagrams)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (mailto:support@kicker.com)

Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

warranty@kicker.com (mailto:warranty@kicker.com)