

# Specifications

## **Speaker Design**

---

2 - way

## **Woofers Size | in [mm]**

---

4x6 [100x160]

## **Tweeter Size | in [mm]**

---

1/2 [13]

## **DC Resistance | ohm**

---

3.3

## **Peak Power (watts, per ANSI/CTA-2031-A)**

---

150

## **Recommended Amplifier Power (watts RMS)**

---

50

## **Sensitivity [SPLo] | dB @ 1W, 1m**

---

88

## **Effective Frequency Range | Hz**

---

50-20k

## **Mounting Hole Diameter | in [mm]**

---

4 x 6 [101x152]

## **Top Mount Depth | in [mm]**

---

5/16 [7]

## **Bottom Mount Depth | in [mm]**

---

1 11/16 [43]

## **Tweeter Protrusion | in [mm]**

---

0

## **Grilles**

---

No

## **Tweeter Magnet Material**

---

Neodymium

## **Tweeter Dome Material**

---

---

PEI [polyether imide]

---

**Tweeter Design**

Balanced dome

---

**Woofers Cone Material**

Polypropylene

---

**Woofers Surround Material**

Polyester foam

## Support



### Manuals

2019 CS Coaxials | Multilingual | Download  
(/app/manuals/mids\_tweets/cs/2019\_CS\_Coax.pdf)

Do you have a different model? Click Here (/product-manuals)



### Support Links

Subwoofer / Speaker FAQ (/faq)



### Contact Support

#### Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (mailto:support@kicker.com)

#### Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

warranty@kicker.com (mailto:warranty@kicker.com)