

- woofer EVC™ (Extended Voice Coil) tech assists with precise linear excursion
- UV-treated poly-foam surround resists heat or direct sunlight
- Large woofer magnet in a heavy-duty motor for ultra-clean bass
- Integrated 2-inch (50mm) midrange drivers gives detailed attention to mid frequencies
- PEI-tweeter construction provides superb clarity
- Neodymium tweeter magnets allow for increased volume in high frequencies
- Steel mesh grilles included for speaker protection

Specifications

Speaker Design

3 - way

Woofer Size | in [mm]

6x9 [160x230]

Mid Size | in [mm]

2 [50]

Tweeter Size | in [mm]

1/2 [13]

DC Resistance | ohm

3.5

Peak Power (watts, per ANSI/CTA-2031-A)

450

Recommended Amplifier Power (watts RMS)

150

Sensitivity [SPLo] | dB @ 1W, 1m

92

Effective Frequency Range | Hz

30-20k

Mounting Hole Diameter | in [mm]

5 5/8 x 8 7/16 [143x215]

Top Mount Depth | in [mm]

7/16 [12]

Bottom Mount Depth | in [mm]

3 3/16 [81]

Tweeter Protrusion | in [mm]

1/16 [1]

Grilles

Yes

Tweeter Magnet Material

Electric Crystal Motor

Tweeter Dome Material

PEI [polyether imide]

Tweeter Design

Balanced dome

Woofers Cone Material

Polypropylene

Woofers Surround Material

Polyester foam

Support



Manuals

2019 CS Coaxials | Multilingual | Download
(/app/manuals/mids_tweets/cs/2019_CS_Coax.pdf)

Do you have a different model? [Click Here \(/product-manuals\)](/product-manuals)



Support Links

Subwoofer / Speaker FAQ (/faq)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (mailto:support@kicker.com)

Warranty Support