



Mounting Options

When it comes to mounting your tweeters, the KS Series 1" Tweeter gives you plenty to choose from!

Specifications

Tweeter [in,mm]

1, 25

Tweeter Dome Material

Silk

Rated Impedance [Ω]

4

Peak Power (watts, per ANSI/CTA-2031-A)

15-150

Recommended Amplifier Power (watts RMS)

75

Sensitivity [1W, 1m]

94

Frequency Response [Hz]

3500-21k

Flush Mount Tweeter Depth [in, mm]

1/2, 12

Flush Mount Tweeter Hole Diameter [in, mm]

1-3/4, 45

High Pass [dB], at Frequency [Hz]

12, 3500

Support



Manuals

2019 KS Tweeters | Multilingual | Download
(/app/manuals/mids_tweets/ks/2019_KS_Tweeter.pdf)

Do you have a different model? Click Here (/product-manuals)



Support Links

Subwoofer / Speaker FAQ (/faq)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (mailto:support@kicker.com)

Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

warranty@kicker.com (mailto:warranty@kicker.com)

 **Sign up for offers**

(/subscribe)

(<http://www.facebook.com/KICKERaudio>)

(http://twitter.com/intent/follow?source=followbutton&variant=1.0&screen_name=KICKERaudio)

(http://www.youtube.com/user/KICKERFANATIC?sub_confirmation=1)