

Specifications

Speaker Design

2-Way

Woofer [in, mm]

6-1/2, 160

Tweeter [in, mm]

3/4, 20

Rated Impedance [Ω]

4

Recommended Amplifier Power [Watts RMS]

15-100

Sensitivity [1W, 1m]

90

Frequency Response [Hz]

43-21k

Mounting Hole Diameter [in, mm]

4-13/16, 123

Top Mount Depth [in, mm]

1-13/16, 46

Bottom Mount Depth [in,mm]

2-3/16, 54

Tweeter Protrusion [in,mm]

5/16, 8

Grilles

Yes

Tweeter Magnet Material

Neodymium

Tweeter Dome Material

Silk

Woofer Cone Material

Polypropylene

Woofer Surround Material

Rubber

Support



Manuals

2020 KS Series | Multilingual | Download (</app/manuals/47KSC.pdf>)

Do you have a different model? Click Here (</product-manuals>)



Support Links

Subwoofer / Speaker FAQ (</faq>)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (<mailto:support@kicker.com>)

Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

warranty@kicker.com (<mailto:warranty@kicker.com>)



Sign up for offers

(</subscribe>)

(<http://www.facebook.com/KICKERaudio>)