

Specifications

Speaker Design

2-Way

Woofers [in, mm]

6 x 9, 160 x 230

Midrange [in, mm]

1, 25

Tweeter [in, mm]

3/4, 20

Rated Impedance [Ω]

4

Recommended Amplifier Power [Watts RMS]

15-150

Sensitivity [1W, 1m]

92

Frequency Response [Hz]

30-21k

Mounting Hole Diameter [in, mm]

5-11/16 x 8-7/16, 144 x 215

Top Mount Depth [in, mm]

3-1/8, 80

Bottom Mount Depth [in, mm]

3-5/8, 92

Tweeter Protrusion [in, mm]

3/16, 5

Grilles

Yes

Tweeter Magnet Material

Neodymium

Tweeter Dome Material

Silk

Woofers Cone Material

Polypropylene

Woofers Surround Material

Rubber

Support



Manuals

2020 KS Series | Multilingual | Download (</app/manuals/47KSC.pdf>)

Do you have a different model? [Click Here \(/product-manuals\)](/product-manuals)



Support Links

[Subwoofer / Speaker FAQ \(/faq\)](/faq)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

[support@kicker.com \(mailto:support@kicker.com\)](mailto:support@kicker.com)

Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

[warranty@kicker.com \(mailto:warranty@kicker.com\)](mailto:warranty@kicker.com)

 **Sign up for offers**

[\(/subscribe\)](/subscribe)