

## Monitor Section

Picture size	6.75inches(diagonal) wide
W x H	151.8mm x 79.7mm, 5-15/16. x 3-1/8 inch
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

## USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16 / 32 / NTFS	
Maximum Power Supply Current	DC 5V = 1.0A	
D/A Converter	24Bit	
Audio Decoder	MP3/ WMA/ WAV/ AAC/ FLAC	
Video Decoder	MPEG1/ MPEG2/ MPEG4/ H.264/ MKV	
Frequency response	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz

## Bluetooth Section

Technology	Bluetooth V4.2
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+8dBm (MAX), Power Class 1
Maximum Communication range	Line of sight approx.10m(32.8ft)
Audio Codec	SBC
Profile	HFP(Hands Free Profile) 1.6
	A2DP(Advanced Audio Distribution Profile)
	AVRCP(Audio/Video Remote Control Profile) 1.5
	PBAP(Phonebook Access Profile)
	SPP(Serial Port Profile)

## DSP Section

Graphics equalizer	BAND	13Band
	frequency(Hz) (BAND1-13)	62.5/ 100/ 160/ 250/ 400/ 630/ 1k/ 1.6k/ 2.5k/ 4k/ 6.3k/ 10k/ 16k
	Gain	-9 to +9 (-9dB to +9dB)

## Monitor Section

Picture size	6.75inches(diagonal) wide
W x H	151.8mm x 79.7mm, 5-15/16. x 3-1/8 inch
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

## USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16 / 32 / NTFS	
Maximum Power Supply Current	DC 5V = 1.0A	
D/A Converter	24Bit	
Audio Decoder	MP3/ WMA/ WAV/ AAC/ FLAC	
Video Decoder	MPEG1/ MPEG2/ MPEG4/ H.264/ MKV	
Frequency response	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz

## Bluetooth Section

Technology	Bluetooth V4.2
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+8dBm (MAX), Power Class 1
Maximum Communication range	Line of sight approx.10m(32.8ft)
Audio Codec	SBC
Profile	HFP(Hands Free Profile) 1.6
	A2DP(Advanced Audio Distribution Profile)
	AVRCP(Audio/Video Remote Control Profile) 1.5
	PBAP(Phonebook Access Profile)
	SPP(Serial Port Profile)

## DSP Section

Graphics equalizer	BAND	13Band
	frequency(Hz) (BAND1-13)	62.5/ 100/ 160/ 250/ 400/ 630/ 1k/ 1.6k/ 2.5k/ 4k/ 6.3k/ 10k/ 16k
	Gain	-9 to +9 (-9dB to +9dB)

## Monitor Section

Picture size	6.75inches(diagonal) wide
W x H	151.8mm x 79.7mm, 5-15/16. x 3-1/8 inch
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

## USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16 / 32 / NTFS	
Maximum Power Supply Current	DC 5V = 1.0A	
D/A Converter	24Bit	
Audio Decoder	MP3/ WMA/ WAV/ AAC/ FLAC	
Video Decoder	MPEG1/ MPEG2/ MPEG4/ H.264/ MKV	
Frequency response	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz

## Bluetooth Section

Technology	Bluetooth V4.2
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+8dBm (MAX), Power Class 1
Maximum Communication range	Line of sight approx.10m(32.8ft)
Audio Codec	SBC
Profile	HFP(Hands Free Profile) 1.6
	A2DP(Advanced Audio Distribution Profile)
	AVRCP(Audio/Video Remote Control Profile) 1.5
	PBAP(Phonebook Access Profile)
	SPP(Serial Port Profile)

## DSP Section

Graphics equalizer	BAND	13Band
	frequency(Hz) (BAND1-13)	62.5/ 100/ 160/ 250/ 400/ 630/ 1k/ 1.6k/ 2.5k/ 4k/ 6.3k/ 10k/ 16k
	Gain	-9 to +9 (-9dB to +9dB)

## Monitor Section

Picture size	6.75inches(diagonal) wide
W x H	151.8mm x 79.7mm, 5-15/16. x 3-1/8 inch
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

## USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16 / 32 / NTFS	
Maximum Power Supply Current	DC 5V = 1.0A	
D/A Converter	24Bit	
Audio Decoder	MP3/ WMA/ WAV/ AAC/ FLAC	
Video Decoder	MPEG1/ MPEG2/ MPEG4/ H.264/ MKV	
Frequency response	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz

## Bluetooth Section

Technology	Bluetooth V4.2
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+8dBm (MAX), Power Class 1
Maximum Communication range	Line of sight approx.10m(32.8ft)
Audio Codec	SBC
Profile	HFP(Hands Free Profile) 1.6
	A2DP(Advanced Audio Distribution Profile)
	AVRCP(Audio/Video Remote Control Profile) 1.5
	PBAP(Phonebook Access Profile)
	SPP(Serial Port Profile)

## DSP Section

Graphics equalizer	BAND	13Band
	frequency(Hz) (BAND1-13)	62.5/ 100/ 160/ 250/ 400/ 630/ 1k/ 1.6k/ 2.5k/ 4k/ 6.3k/ 10k/ 16k
	Gain	-9 to +9 (-9dB to +9dB)

## Monitor Section

Picture size	6.75inches(diagonal) wide
W x H	151.8mm x 79.7mm, 5-15/16. x 3-1/8 inch
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

## USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16 / 32 / NTFS	
Maximum Power Supply Current	DC 5V = 1.0A	
D/A Converter	24Bit	
Audio Decoder	MP3/ WMA/ WAV/ AAC/ FLAC	
Video Decoder	MPEG1/ MPEG2/ MPEG4/ H.264/ MKV	
Frequency response	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz

## Bluetooth Section

Technology	Bluetooth V4.2
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+8dBm (MAX), Power Class 1
Maximum Communication range	Line of sight approx.10m(32.8ft)
Audio Codec	SBC
Profile	HFP(Hands Free Profile) 1.6
	A2DP(Advanced Audio Distribution Profile)
	AVRCP(Audio/Video Remote Control Profile) 1.5
	PBAP(Phonebook Access Profile)
	SPP(Serial Port Profile)

## DSP Section

Graphics equalizer	BAND	13Band
	frequency(Hz) (BAND1-13)	62.5/ 100/ 160/ 250/ 400/ 630/ 1k/ 1.6k/ 2.5k/ 4k/ 6.3k/ 10k/ 16k
	Gain	-9 to +9 (-9dB to +9dB)

## Monitor Section

Picture size	6.75inches(diagonal) wide
W x H	151.8mm x 79.7mm, 5-15/16. x 3-1/8 inch
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

## USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16 / 32 / NTFS	
Maximum Power Supply Current	DC 5V = 1.0A	
D/A Converter	24Bit	
Audio Decoder	MP3/ WMA/ WAV/ AAC/ FLAC	
Video Decoder	MPEG1/ MPEG2/ MPEG4/ H.264/ MKV	
Frequency response	96k Sampling	20 - 20,000 Hz
	48k Sampling	20 - 20,000 Hz
	44.1k Sampling	20 - 20,000 Hz

## Bluetooth Section

Technology	Bluetooth V4.2
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+8dBm (MAX), Power Class 1
Maximum Communication range	Line of sight approx.10m(32.8ft)
Audio Codec	SBC
Profile	HFP(Hands Free Profile) 1.6
	A2DP(Advanced Audio Distribution Profile)
	AVRCP(Audio/Video Remote Control Profile) 1.5
	PBAP(Phonebook Access Profile)
	SPP(Serial Port Profile)

## DSP Section

Graphics equalizer	BAND	13Band
	frequency(Hz) (BAND1-13)	62.5/ 100/ 160/ 250/ 400/ 630/ 1k/ 1.6k/ 2.5k/ 4k/ 6.3k/ 10k/ 16k
	Gain	-9 to +9 (-9dB to +9dB)