

2Way X'Over	HIGH PASS FILTER frequency	Through/30/40/50/60/70/80/90/100/120/150/180/220/250[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
	LOW PASS FILTER frequency	30/40/50/60/70/80/90/100/120/150/180/220/250/Through[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
Position	Front / Rear /Subwoofer Delay	0 - 20.01ft (0.03or0.04ft Step)
	Gain	-8 to 0dB
	Subwoofer Level	-50 to +10dB

Digital FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Frequency Response (±3.0 dB)	20Hz - 20kHz
S/N	80dB (STEREO)

Digital AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Frequency Response (±3.0 dB)	40Hz - 15kHz
S/N	80dB (STEREO)

FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Usable sensitivity	9.3dBf
S/N30dB	0.8μV/75Ω
Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms

E C L	2Way X'Over	HIGH PASS FILTER frequency	Through/30/40/50/60/70/80/90/100/120/150/180/220/250[Hz]
		SLOPE	-6/-12/-18/-24[dB/Oct.]
		LOW PASS FILTER frequency	30/40/50/60/70/80/90/100/120/150/180/220/250/Through[Hz]
		SLOPE	-6/-12/-18/-24[dB/Oct.]
Position	Front / Rear /Subwoofer Delay	0 - 20.01ft (0.03or0.04ft Step)	
	Gain	-8 to 0dB	
	Subwoofer Level	-50 to +10dB	

Digital FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Frequency Response (±3.0 dB)	20Hz - 20kHz
S/N	80dB (STEREO)

Digital AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Frequency Response (±3.0 dB)	40Hz - 15kHz
S/N	80dB (STEREO)

FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Usable sensitivity	9.3dBf
S/N30dB	0.8μV/75Ω
Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms

2Way X'Over	HIGH PASS FILTER frequency	Through/30/40/50/60/70/80/90/100/120/150/180/220/250[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
	LOW PASS FILTER frequency	30/40/50/60/70/80/90/100/120/150/180/220/250/Through[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
Position	Front / Rear /Subwoofer Delay	0 - 20.01ft (0.03or0.04ft Step)
	Gain	-8 to 0dB
	Subwoofer Level	-50 to +10dB

Digital FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Frequency Response (±3.0 dB)	20Hz - 20kHz
S/N	80dB (STEREO)

Digital AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Frequency Response (±3.0 dB)	40Hz - 15kHz
S/N	80dB (STEREO)

FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Usable sensitivity	9.3dBf
S/N30dB	0.8μV/75Ω
Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms

2Way X'Over	HIGH PASS FILTER frequency	Through/30/40/50/60/70/80/90/100/120/150/180/220/250[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
	LOW PASS FILTER frequency	30/40/50/60/70/80/90/100/120/150/180/220/250/Through[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
Position	Front / Rear /Subwoofer Delay	0 - 20.01ft (0.03or0.04ft Step)
	Gain	-8 to 0dB
	Subwoofer Level	-50 to +10dB

Digital FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Frequency Response (±3.0 dB)	20Hz - 20kHz
S/N	80dB (STEREO)

Digital AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Frequency Response (±3.0 dB)	40Hz - 15kHz
S/N	80dB (STEREO)

FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Usable sensitivity	9.3dBf
S/N30dB	0.8μV/75Ω
Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms

2Way X'Over	HIGH PASS FILTER frequency	Through/30/40/50/60/70/80/90/100/120/150/180/220/250[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
	LOW PASS FILTER frequency	30/40/50/60/70/80/90/100/120/150/180/220/250/Through[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
Position	Front / Rear /Subwoofer Delay	0 - 20.01ft (0.03or0.04ft Step)
	Gain	-8 to 0dB
	Subwoofer Level	-50 to +10dB

Digital FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Frequency Response (±3.0 dB)	20Hz - 20kHz
S/N	80dB (STEREO)

Digital AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Frequency Response (±3.0 dB)	40Hz - 15kHz
S/N	80dB (STEREO)

FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Usable sensitivity	9.3dBf
S/N30dB	0.8μV/75Ω
Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms

2Way X'Over	HIGH PASS FILTER frequency	Through/30/40/50/60/70/80/90/100/120/150/180/220/250[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
	LOW PASS FILTER frequency	30/40/50/60/70/80/90/100/120/150/180/220/250/Through[Hz]
	SLOPE	-6/-12/-18/-24[dB/Oct.]
Position	Front / Rear /Subwoofer Delay	0 - 20.01ft (0.03or0.04ft Step)
	Gain	-8 to 0dB
	Subwoofer Level	-50 to +10dB

Digital FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Frequency Response (±3.0 dB)	20Hz - 20kHz
S/N	80dB (STEREO)

Digital AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Frequency Response (±3.0 dB)	40Hz - 15kHz
S/N	80dB (STEREO)

FM

Frequency Range (Frequency step)	87.9MHz - 107.9MHz (200kHz)
Usable sensitivity	9.3dBf
S/N30dB	0.8μV/75Ω
Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms