

ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$	
	Peak Input Power (W)	650W	
	RMS Input Power (W) CTA standards	150W	
	Sensitivity (dB at 1m) CTA standards	88dB	
	Frequency Response(Hz) CTA standards	58-22000Hz	
Woofer	Diaphragm / Color	PP Cone	Black
	Size	153x229mm	6x9 inch
	Surround	Urethane	
	Basket	Steel	
	Magnet	Ferrite	$\phi$ 100xt15
Tweeter	Diaphragm / Color	Balanced Dome	Matte Black
	Size	44mm	1-3/4 inch
	Magnet	Ferrite	
Super Tweeter1	Diaphragm / Color	Cermic	Silver
	Size	20mm	4/5 inch
Super Tweeter2	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Super Tweeter3	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Dimension	Width (w_Gr)	266.1 mm	10-1/2 in.
	Width (w/o_Gr)	236.4 mm	9-5/16 in.
	Height (w_Gr)	197.3 mm	7-3/4 in.
	Height (w/o Gr)	164 mm	6-7/16 in.

ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$	
	Peak Input Power (W)	650W	
	RMS Input Power (W) CTA standards	150W	
	Sensitivity (dB at 1m) CTA standards	88dB	
	Frequency Response(Hz) CTA standards	58-22000Hz	
Woofer	Diaphragm / Color	PP Cone	Black
	Size	153x229mm	6x9 inch
	Surround	Urethane	
	Basket	Steel	
	Magnet	Ferrite	$\phi$ 100xt15
Tweeter	Diaphragm / Color	Balanced Dome	Matte Black
	Size	44mm	1-3/4 inch
	Magnet	Ferrite	
Super Tweeter1	Diaphragm / Color	Cermic	Silver
	Size	20mm	4/5 inch
Super Tweeter2	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Super Tweeter3	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Dimension	Width (w_Gr)	266.1 mm	10-1/2 in.
	Width (w/o_Gr)	236.4 mm	9-5/16 in.
	Height (w_Gr)	197.3 mm	7-3/4 in.
	Height (w/o Gr)	164 mm	6-7/16 in.

ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$	
	Peak Input Power (W)	650W	
	RMS Input Power (W) CTA standards	150W	
	Sensitivity (dB at 1m) CTA standards	88dB	
	Frequency Response(Hz) CTA standards	58-22000Hz	
Woofer	Diaphragm / Color	PP Cone	Black
	Size	153x229mm	6x9 inch
	Surround	Urethane	
	Basket	Steel	
	Magnet	Ferrite	$\phi$ 100x15
Tweeter	Diaphragm / Color	Balanced Dome	Matte Black
	Size	44mm	1-3/4 inch
	Magnet	Ferrite	
Super Tweeter1	Diaphragm / Color	Ceramic	Silver
	Size	20mm	4/5 inch
Super Tweeter2	Diaphragm / Color	Ceramic	Silver
	Size	12mm	1/2 inch
Super Tweeter3	Diaphragm / Color	Ceramic	Silver
	Size	12mm	1/2 inch
Dimension	Width (w_Gr)	266.1 mm	10-1/2 in.
	Width (w/o_Gr)	236.4 mm	9-5/16 in.
	Height (w_Gr)	197.3 mm	7-3/4 in.
	Height (w/o Gr)	164 mm	6-7/16 in.

ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$	
	Peak Input Power (W)	650W	
	RMS Input Power (W) CTA standards	150W	
	Sensitivity (dB at 1m) CTA standards	88dB	
	Frequency Response(Hz) CTA standards	58-22000Hz	
Woofer	Diaphragm / Color	PP Cone	Black
	Size	153x229mm	6x9 inch
	Surround	Urethane	
	Basket	Steel	
	Magnet	Ferrite	$\phi$ 100x15
Tweeter	Diaphragm / Color	Balanced Dome	Matte Black
	Size	44mm	1-3/4 inch
	Magnet	Ferrite	
Super Tweeter1	Diaphragm / Color	Cermic	Silver
	Size	20mm	4/5 inch
Super Tweeter2	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Super Tweeter3	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Dimension	Width (w_Gr)	266.1 mm	10-1/2 in.
	Width (w/o_Gr)	236.4 mm	9-5/16 in.
	Height (w_Gr)	197.3 mm	7-3/4 in.
	Height (w/o Gr)	164 mm	6-7/16 in.

ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$	
	Peak Input Power (W)	650W	
	RMS Input Power (W) CTA standards	150W	
	Sensitivity (dB at 1m) CTA standards	88dB	
	Frequency Response(Hz) CTA standards	58-22000Hz	
Woofer	Diaphragm / Color	PP Cone	Black
	Size	153x229mm	6x9 inch
	Surround	Urethane	
	Basket	Steel	
	Magnet	Ferrite	$\phi$ 100x15
Tweeter	Diaphragm / Color	Balanced Dome	Matte Black
	Size	44mm	1-3/4 inch
	Magnet	Ferrite	
Super Tweeter1	Diaphragm / Color	Cermic	Silver
	Size	20mm	4/5 inch
Super Tweeter2	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Super Tweeter3	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Dimension	Width (w_Gr)	266.1 mm	10-1/2 in.
	Width (w/o_Gr)	236.4 mm	9-5/16 in.
	Height (w_Gr)	197.3 mm	7-3/4 in.
	Height (w/o Gr)	164 mm	6-7/16 in.

ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$	
	Peak Input Power (W)	650W	
	RMS Input Power (W) CTA standards	150W	
	Sensitivity (dB at 1m) CTA standards	88dB	
	Frequency Response(Hz) CTA standards	58-22000Hz	
Woofer	Diaphragm / Color	PP Cone	Black
	Size	153x229mm	6x9 inch
	Surround	Urethane	
	Basket	Steel	
	Magnet	Ferrite	$\phi$ 100xt15
Tweeter	Diaphragm / Color	Balanced Dome	Matte Black
	Size	44mm	1-3/4 inch
	Magnet	Ferrite	
Super Tweeter1	Diaphragm / Color	Cermic	Silver
	Size	20mm	4/5 inch
Super Tweeter2	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Super Tweeter3	Diaphragm / Color	Cermic	Silver
	Size	12mm	1/2 inch
Dimension	Width (w_Gr)	266.1 mm	10-1/2 in.
	Width (w/o_Gr)	236.4 mm	9-5/16 in.
	Height (w_Gr)	197.3 mm	7-3/4 in.
	Height (w/o Gr)	164 mm	6-7/16 in.