

MODEL NAME		KFC-X3C		KFC-X2C	
ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$		4 $\Omega$	
	Peak Input Power (W)	120W		120W	
	RMS Input Power (W) CTA standards	50W		50W	
	Sensitivity (dB at 1m) CTA standards	83dB		83dB	
	Frequency Response(Hz) CTA standards	800-23,000Hz		800-20,000Hz	
Midrange	Diaphragm	PP Cone		PP Cone	+Sub Cone
	Size	30mm	3-1/2 inch	30mm	2-3/4 inch
	Surround	Rubber		Cloth	
	Basket	Steel		Plastic	
	Magnet	Ferrite	$\phi$ 65x18	Ferrite	$\phi$ 50x18
Tweeter	Diaphragm	Balanced Dome			
	Size	25mm	1 inch		
	Magnet	Neodymium			
Newtwork	Midrange	HPF	-6dB/oct, 850Hz	HPF	-6dB/oct, 850Hz
Dimension	Midrange				
	Width	113mm	4-7/16 in.	103mm	4-1/16 in.
	Height	87 mm	3-7/16 in.	71.5 mm	2-13/16 in.
	Top Height	44 mm	1-3/4 in.	40 mm	1-9/16 in.
	Cutout Diameter	$\phi$ 75.5 mm	$\phi$ 3 in.	$\phi$ 62 mm	$\phi$ 2-7/16 in.
	Height from the mouning surface	8 mm	5/16 in.	6 mm	1/4 in.
	Mounting Depth	36 mm	1-7/16 in.	34 mm	1-5/16 in.

MODEL NAME		KFC-X3C		KFC-X2C	
ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$		4 $\Omega$	
	Peak Input Power (W)	120W		120W	
	RMS Input Power (W) CTA standards	50W		50W	
	Sensitivity (dB at 1m) CTA standards	83dB		83dB	
	Frequency Response(Hz) CTA standards	800-23,000Hz		800-20,000Hz	
Midrange	Diaphragm	PP Cone		PP Cone	+Sub Cone
	Size	30mm	3-1/2 inch	30mm	2-3/4 inch
	Surround	Rubber		Cloth	
	Basket	Steel		Plastic	
	Magnet	Ferrite	$\phi$ 65x18	Ferrite	$\phi$ 50x18
Tweeter	Diaphragm	Balanced Dome			
	Size	25mm	1 inch		
	Magnet	Neodymium			
Newtwork	Midrange	HPF	-6dB/oct, 850Hz	HPF	-6dB/oct, 850Hz
Dimension	Midrange				
	Width	113mm	4-7/16 in.	103mm	4-1/16 in.
	Height	87 mm	3-7/16 in.	71.5 mm	2-13/16 in.
	Top Height	44 mm	1-3/4 in.	40 mm	1-9/16 in.
	Cutout Diameter	$\phi$ 75.5 mm	$\phi$ 3 in.	$\phi$ 62 mm	$\phi$ 2-7/16 in.
	Height from the mouning surface	8 mm	5/16 in.	6 mm	1/4 in.
	Mounting Depth	36 mm	1-7/16 in.	34 mm	1-5/16 in.

MODEL NAME		KFC-X3C		KFC-X2C	
ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$		4 $\Omega$	
	Peak Input Power (W)	120W		120W	
	RMS Input Power (W) CTA standards	50W		50W	
	Sensitivity (dB at 1m) CTA standards	83dB		83dB	
	Frequency Response(Hz) CTA standards	800-23,000Hz		800-20,000Hz	
Midrange	Diaphragm	PP Cone		PP Cone	+Sub Cone
	Size	30mm	3-1/2 inch	30mm	2-3/4 inch
	Surround	Rubber		Cloth	
	Basket	Steel		Plastic	
	Magnet	Ferrite	$\phi$ 65x18	Ferrite	$\phi$ 50x18
Tweeter	Diaphragm	Balanced Dome			
	Size	25mm	1 inch		
	Magnet	Neodymium			
Newtwork	Midrange	HPF	-6dB/oct, 850Hz	HPF	-6dB/oct, 850Hz
Dimension	Midrange				
	Width	113mm	4-7/16 in.	103mm	4-1/16 in.
	Height	87 mm	3-7/16 in.	71.5 mm	2-13/16 in.
	Top Height	44 mm	1-3/4 in.	40 mm	1-9/16 in.
	Cutout Diameter	$\phi$ 75.5 mm	$\phi$ 3 in.	$\phi$ 62 mm	$\phi$ 2-7/16 in.
	Height from the mouning surface	8 mm	5/16 in.	6 mm	1/4 in.
	Mounting Depth	36 mm	1-7/16 in.	34 mm	1-5/16 in.

MODEL NAME		KFC-X3C		KFC-X2C	
ELECTRICAL	Impedance( $\Omega$ )	4 $\Omega$		4 $\Omega$	
	Peak Input Power (W)	120W		120W	
	RMS Input Power (W) CTA standards	50W		50W	
	Sensitivity (dB at 1m) CTA standards	83dB		83dB	
	Frequency Response(Hz) CTA standards	800-23,000Hz		800-20,000Hz	
Midrange	Diaphragm	PP Cone		PP Cone	+Sub Cone
	Size	30mm	3-1/2 inch	30mm	2-3/4 inch
	Surround	Rubber		Cloth	
	Basket	Steel		Plastic	
	Magnet	Ferrite	$\phi$ 65x18	Ferrite	$\phi$ 50x18
Tweeter	Diaphragm	Balanced Dome			
	Size	25mm	1 inch		
	Magnet	Neodymium			
Newtwork	Midrange	HPF	-6dB/oct, 850Hz	HPF	-6dB/oct, 850Hz
Dimension	Midrange				
	Width	113mm	4-7/16 in.	103mm	4-1/16 in.
	Height	87 mm	3-7/16 in.	71.5 mm	2-13/16 in.
	Top Height	44 mm	1-3/4 in.	40 mm	1-9/16 in.
	Cutout Diameter	$\phi$ 75.5 mm	$\phi$ 3 in.	$\phi$ 62 mm	$\phi$ 2-7/16 in.
	Height from the mouning surface	8 mm	5/16 in.	6 mm	1/4 in.
	Mounting Depth	36 mm	1-7/16 in.	34 mm	1-5/16 in.