

CTA-2006 Primary Ratings	Power Output	300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	85dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1000W
Rated Power Output at 14.4V	A/B (4 Ohms)	-
	A/B (2 Ohms)	-
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	-
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-200Hz (+0dB, -3dB)
	Frequency Response	-
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	-
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct
	High-Pass Filter	-
	Bass Boost	40Hz, 0dB - +18dB
	Infrasonic Filter	25Hz, -24dB
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)8-3/8" x (H)2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 213cm x (H) 53cm x (D) 149cm

CTA-2006 Primary Ratings	Power Output	300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	85dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1000W
Rated Power Output at 14.4V	A/B (4 Ohms)	-
	A/B (2 Ohms)	-
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	-
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-200Hz (+0dB, -3dB)
	Frequency Response	-
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	-
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct
	High-Pass Filter	-
	Bass Boost	40Hz, 0dB - +18dB
	Infrasonic Filter	25Hz, -24dB
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)8-3/8" x (H)2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 213cm x (H) 53cm x (D) 149cm

CTA-2006 Primary Ratings	Power Output	300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	85dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1000W
Rated Power Output at 14.4V	A/B (4 Ohms)	-
	A/B (2 Ohms)	-
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	-
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-200Hz (+0dB, -3dB)
	Frequency Response	-
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	-
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct
	High-Pass Filter	-
	Bass Boost	40Hz, 0dB - +18dB
	Infrasonic Filter	25Hz, -24dB
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)8-3/8" x (H)2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 213cm x (H) 53cm x (D) 149cm

CTA-2006 Primary Ratings	Power Output	300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	85dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1000W
Rated Power Output at 14.4V	A/B (4 Ohms)	-
	A/B (2 Ohms)	-
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	-
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-200Hz (+0dB, -3dB)
	Frequency Response	-
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	-
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct
	High-Pass Filter	-
	Bass Boost	40Hz, 0dB - +18dB
	Infrasonic Filter	25Hz, -24dB
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)8-3/8" x (H)2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 213cm x (H) 53cm x (D) 149cm

CTA-2006 Primary Ratings	Power Output	300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	85dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1000W
Rated Power Output at 14.4V	A/B (4 Ohms)	-
	A/B (2 Ohms)	-
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	-
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-200Hz (+0dB, -3dB)
	Frequency Response	-
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	-
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct
	High-Pass Filter	-
	Bass Boost	40Hz, 0dB - +18dB
	Infrasonic Filter	25Hz, -24dB
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)8-3/8" x (H)2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 213cm x (H) 53cm x (D) 149cm