

## XR-1700P

Model Name		XR-1700P	
System		Component speaker	
Power Handling	KITS Spec		
	Peak Input Power	280W	
	Maximum Input Power	100W	
	Rated Power	50W	
	CTA Spec (CTA-2031 Compliant)		
	RMS Power	80Watts RMS	
	Impedance	4Ω	
	Sensitivity	86dB/ W at 1 m	
	Frequency Response	57 Hz~20,000 Hz	
	Woofers	Diaphragm	Paper Cone
Size		Oversized 165 mm	6-1/2 inch
Surround		Rubber	
Basket		Steel	
Magnet		Ferrite	φ90 x t15
Tweeter	Diaphragm	Soft Dome	
	Size	30 mm	1-3/16 inch
	Magnet	Nd	Up to Engineer

Dimension	Woofers		
	with Grille		
	Width	180.0 mm	7-1/16 inch
	Height	180.0 mm	7-1/16 inch
	Depth	84.0 mm	3-5/16 inch
	without Grille		
	Width	158.0 mm	6-1/4 inch
	Height	158.0 mm	6-1/4 inch
	Depth	72.3 mm	2-7/8 inch
	Cut-out Diameter	126.0 mm	4-15/16 inch
	Mounting Depth	59.0 mm	2-5/16 inch
	Tweeter (Component)		
	Width	53.0 mm	2-1/16 inch
	Height	53.0 mm	2-1/16 inch
	Depth	26.7 mm	1-1/6 inch
Accessory	Grille	2 pcs	
	Grille Holder	○	
	Punching Net	○	
	Network	BOX TYPE	2 pcs
	Tweeter	PSW / ATT(2Way)	-12dB/oct
	Woofers	-12dB/oct	
	Tweeter Bracket		
	Mounting HardWare (for 30mm)	○	2 pcs
	Angle Mount (for 30mm)	○	2 pcs
	GM Bracket	2 pcs	
	Screw sets		

Binding Head Tapping Screw	φ4 x 25 mm	12 pcs
Binding Head Tapping Screw	φ4 x 6 mm	8 pcs
Binding Head Tapping Screw	φ3 x 16 mm	4 pcs
Binding Head Machine Screw	M3 x 6 mm	2 pcs
Speed Nut	φ3	4 pcs
Speed Nut	φ4	12 pcs
Adhesive Tape	○	1 set



**KENWOOD**

CAR ENTERTAINMENT

Communications

**eXcelon**

- Network Navigation
- Navigation
- Multimedia
- Receivers
- Subwoofer
- Speakers
- Amplifiers
- Accessories

**Marine**

- 1 DIN CDR
- Digital Media Receivers
- Amplifiers
- Speakers
- Accessories

**Navigation  
Multimedia**

- Navigation
- Multimedia
- Accessories

**Amplifiers**

- Amplifiers
- Compact Amplifiers

**Dashboard Camera**

**Support**

**Receivers**

- 1 DIN CDR
- DUAL DIN Receivers
- Digital Media Receivers
- Accessories

**Speakers**

- Subwoofer
- Performance Series
- Sports Series
- Custom Fit & Tweeter