


# FOR SERVICE TECHNICIAN'S USE ONLY

Do not discard

**⚠ DANGER**




**Electrical Shock Hazard**

**Only authorized technicians should perform diagnostic voltage measurements.**

**After performing voltage measurements, disconnect power before servicing.**

**Failure to follow these instructions can result in death or electrical shock.**

**⚠ WARNING**



**Electrical Shock Hazard**

**Disconnect power before servicing.**

**Replace all parts and panels before operating.**

**Failure to do so can result in death or electrical shock.**

**Voltage Measurement Safety Information**

**When performing live voltage measurements, you must do the following:**

- **Verify the controls are in the off position so that the appliance does not start when energized.**
- **Allow enough space to perform the voltage measurements without obstructions.**
- **Keep other people a safe distance away from the appliance to prevent potential injury.**
- **Always use the proper testing equipment.**
- **After voltage measurements, always disconnect power before servicing.**

## PRECAUTIONS TO BE OBSERVED BEFORE AND DURING SERVICING TO AVOID POSSIBLE EXPOSURE TO EXCESSIVE MICROWAVE ENERGY

- a. Do not operate or allow the oven to be operated with the door open.
- b. Make the following safety checks on all ovens to be serviced before activating the magnetron or other microwave source, and make repairs as necessary:
  1. Interlock Operation
  2. Proper Door Closing
  3. Seal and Sealing Surfaces (Arcing, Wear and Other Damage)
  4. Damage to or Loosening of Hinges and Latches
  5. Evidence of Dropping or Abuse
- c. Before turning on microwave power for any service test or inspection within the microwave generating compartments, check the magnetron, wave guide or transmission line, and cavity for proper alignment, integrity and connections.
- d. Any defective or misadjusted components in the interlock, monitor, door seal, and microwave generation and transmission systems shall be repaired, replaced, or adjusted by procedures described in this manual before the oven is released to the owner.
- e. A microwave leakage check to verify compliance with the Federal Performance Standard should be performed on each oven prior to release to the owner.
- f. Do not attempt to operate the oven if the door glass is broken.



# FOR SERVICE TECHNICIAN'S USE ONLY

## FAILURE CODE INDICATIONS

**NOTE:** Many of the problems listed in the chart below may be solved by power cycling: Unplug microwave oven or disconnect power. After 1 minute, plug in microwave oven or reconnect power.

Display	Likely Failure Condition	Recommended Repair Procedure
Flashing colon ":"	Power failure	After a power failure, the colon ":" will be flashing. Press any key to end this indication. The colon will then be steady when in Standby mode.
F2E1	Touch panel failure	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Replace touch panel.</li> <li>3. Replace all parts and panels before operating.</li> </ol> <ol style="list-style-type: none"> <li>4. Plug in microwave oven or reconnect power.</li> <li>5. If problem persists, refer to "ACU Pin Voltage Matrix."</li> </ol>
F1E4	MW relay	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Check wiring to Relay 4903.</li> <li>3. Check to see if the relay (4903 on ACU) contact has welded closed.</li> </ol> <ol style="list-style-type: none"> <li>4. Replace all parts and panels before operating.</li> <li>5. Plug in microwave oven or reconnect power.</li> <li>6. If problem persists, refer to "ACU Pin Voltage Matrix" to check EP1-2 (Door), EP1-1 (N), and EP1-4 (L).</li> </ol>

## PRIMARY, SECONDARY, MONITOR AND DOOR INTERLOCK SWITCH CHECKOUT PROCEDURES

**IMPORTANT:** Before checking the interlock switches, unplug microwave oven or disconnect power. Be sure to disconnect all of the wires at the switch being tested before making any continuity readings.

**NOTE:** The Secondary Interlock Switch, Monitor Interlock Switch, Primary Interlock Switch and Door Interlock Switch are mounted in the door lock switch cradle. All the interlock switches can be identified by the wire colors that are connected to the terminals of the switches. See the chart below for wire color designation.


Switch	Check By	Door Open	Door Closed
Primary Interlock	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Disconnect the wires at the Primary Interlock Switch.</li> <li>3. Check from the common terminal (black/brown wires) to the normally open terminal (black/white wires).</li> <li>4. Reconnect wires to switch.</li> </ol>	-	+
Monitor Interlock	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Disconnect the wires at the Monitor Interlock Switch.</li> <li>3. Check from the common terminal (white wire) to the normally closed terminal (blue/white wires).</li> <li>4. Reconnect wires to switch.</li> </ol>	+	-
Secondary Interlock	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Disconnect the wires at the Secondary Interlock Switch.</li> <li>3. Check from the common terminal (white/blue wires) to the normally open terminal (blue/blue wires).</li> <li>4. Reconnect wires to switch.</li> </ol>	-	+
Door Interlock	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Disconnect the wires at the Door Interlock Switch.</li> <li>3. Check from the common terminal (blue wire) to the normally closed terminal (orange wire).</li> <li>4. Reconnect wires to switch.</li> </ol>	+	-

(+) Continuity (-) No Continuity


**NOTES:**

- These diagrams are not intended to show a complete circuit; they represent the position of switches during "DOOR OPEN" or "DOOR CLOSED" (continuity checks only).
- Interlock and Monitor switches cannot be adjusted and all these switches should be replaced if any one of them is found to be defective. After replacing interlock/monitor switches, reconnect wires to switch and check for continuity.

**Door Closed**



**Door Open**



# FOR SERVICE TECHNICIAN'S USE ONLY

## NOT HEATING TROUBLESHOOTING INSTRUCTION

**IMPORTANT:** High voltage is present at the magnetron and H.V. capacitor terminals. Avoid direct contact when power is connected to these components to avoid serious injury or possible death. Always be sure that the high-voltage capacitor is discharged before accessing any of these components.

For a no-heat condition, refer to the following step-by-step instructions:

1. Unplug microwave oven or disconnect power.
2. Discharge the high-voltage capacitor.
3. Disconnect the high-voltage transformer primary windings.
4. Attach the voltmeter leads to the high-voltage transformer primary input wires.
5. Plug in microwave oven or reconnect power.
6. Close door and program the microwave oven to operate for 30 seconds.
7. Press START.
8. Check the input voltage at the high-voltage transformer primary input wires. If the voltage is not close to the rating voltage 120 +/-15 VAC, unplug microwave oven or disconnect power. Check the circuitry as follows:
  - Measure resistance of the fuse, microswitches, and thermostats. Replace any failed components (refer to the wiring diagram).

- Check for loose terminals (refer to the wiring diagram). Check all of the terminals on the main route from the power supply to the high-voltage transformer.
  - Check for loose or failed connectors on the ACU (EP1, EP2). If these check out OK, plug in microwave oven or reconnect power.
  - Check for ACU failure. Refer to "ACU Pin Voltage Matrix."
9. If the input voltage at the high-voltage transformer primary input wires is close to the rating voltage 120 +/-15 VAC, unplug microwave oven or disconnect power.
  10. Check the power supply components. Refer to "Component Tests."
    - High-voltage transformer
    - High-voltage capacitor
    - High-voltage diode
  11. If the power supply components check out OK, check the connection between the magnetron and the high-voltage transformer.
  12. If all of the components check out OK, replace the magnetron.
  13. Reconnect the high-voltage transformer primary windings.

## ACU PIN VOLTAGE MATRIX

**Check for proper voltage by completing the following steps:**

1. Unplug microwave oven or disconnect power.
2. Connect voltage measurement equipment to the terminal listed below (EP1-1 is neutral).
3. Plug in microwave oven or reconnect power and confirm voltage reading.
4. Unplug microwave oven or disconnect power.

**NOTE:** For 50V and over, the tolerance is +/-15V. For 0V, the tolerance is +/-3V.

**Abbreviations**


HL - Hood Light	N - Neutral	CL - Cavity Light	HF - Hood Fan	L - Line Voltage	TT - Turntable Motor
-----------------	-------------	-------------------	---------------	------------------	----------------------

**NOTE:** When checking voltage readings on ACU, connect the neutral test lead of voltmeter to connector EP1-1. Use the positive test lead to probe connectors designated below.

Pin Name	Wire Color	MW Oven Plugged In—Sitting Idle—ACV Readings						MW Oven Running—ACV Readings
		Power On, Door Closed	Power On, Door Open	Hood Fan Motor— High	Hood Fan Motor— Medium	Hood Light— High	Hood Light— Low	
EP1-1 (N)	Green	0	0	0	0	0	0	0
EP1-2 (Door)	Orange	0	120	0/120*	0/120*	0/120*	0/120*	120
EP1-3 (TT/CL)	Red/Gray	0	120	0	0	0	0	120
EP1-4 (L)	Brown	120	120	120	120	120	120	120
EP2-1 (HF-HI)	Black	0	0	120	13	0	0	13
EP2-2 (HF-LO)	White	0	0	13	120	0	0	120
EP2-3 (HL)	Yellow	0	0	0	0	120	66	0

\*Door Closed/Open

## CONNECTORS ON ACU



**NOTE:** There are purposely empty terminals between each of the numbered terminals on EP1 and EP2 connectors.

# FOR SERVICE TECHNICIAN'S USE ONLY

## TOUCH PANEL

### Touch Panel and ACU Test

The microwave hood combination is provided with a self-diagnostic routine that can be accessed through the touch keypad.

#### To initiate this routine:

1. Plug in microwave oven or reconnect power, and then press Cancel button to standby (“:”).
2. Close door, then press CANCEL - CANCEL - START within 3 seconds.

#### Key Tables for Test Mode

Key Name	Function	Display	Buzzer
Start	-	01	1 beep
Light	-	03	1 beep
Fan/Vent Fan	-	04	1 beep
Clock	-	06	1 beep
Timer Set/Off	-	07	1 beep
Add 30 Sec	-	09	1 beep
Cook Time	-	10	1 beep
Cook Power	-	11	1 beep
Cook	-	13	1 beep
Reheat	-	14	1 beep
Defrost	-	15	1 beep
Popcorn	-	18	1 beep
0	LED Grid Check	(see note following table)	1 beep

All LED segments will be lit to indicate the Test mode has been entered.

**NOTE:** If the Cancel button is pressed during this diagnostic routine, you will exit the Test mode.


Key Name	Function	Display	Buzzer
1	Cavity Light and Turntable Motor* ON—Relay 4901	33	1 beep
2	Hood (Cooktop) Light ON (High)—Triac 7104	34	1 beep
3	Microwave Oven ON for 10 Seconds—Relay 4903	35	1 beep
4	HF NTC Thermistor	100-977**	1 beep
5	-	37	1 beep
6	-	38	1 beep
7	Vent Fan ON (Low Speed) – Relay 4905	39	1 beep
8	Hood (Cooktop) Light ON (Night)—Triac 7104	40	1 beep
9	Vent Fan ON (High Speed)—Relay 4902	41	1 beep
Cancel	Exit Test Mode	-	1 beep

\*Turntable motor does not turn on with cavity light when door is open.

\*\*Varies, depending on room temperature.

**NOTE:** Icons (symbols) flash, “8” will flash, and then populate display from right to left.

## PARTS LAYOUT (NOT TO SCALE)



- A. Hood exhaust fan motor
- B. Motor capacitor
- C. H.V. capacitor
- D. Magnetron
- E. Magnetron thermostat—opens at 257°F (125°C) or 221°F (105°C), closes at 185°F (85°C)
- F. Cavity thermostat—non-resettable
- G. HF NTC thermistor
- H. H.V. transformer
- I. H.V. diode

- J. ACU
- K. Touch panel
- L. Secondary interlock switch
- L1. Door interlock switch
- M. Monitor interlock switch
- N. Primary interlock switch
- O. Light holders
- P. Hood (cooktop) light
- Q. Turntable motor
- R. Cavity light
- S. Main fuse (20 amp)
- T. AC filter board

# FOR SERVICE TECHNICIAN'S USE ONLY

## POWER OUTPUT MEASUREMENT

The power output of the magnetron can be measured using the following “Voltage Measurement” and “Output Test”. Before you perform the test:

- Make sure that the oven cavity is cool and clean.
- Check the line voltage at the wall outlet while microwave oven is operating. See “Voltage Measurement at Power Source”.

#### Tools Needed

- 2-cup measuring cup
- Thermometer
- Voltmeter/ohmmeter


#### Voltage Measurement at Power Source

1. Fill the measuring cup with 2 cups (500 mL) of tap water.
2. Place in the center of the microwave oven cavity.
3. Operate the microwave oven on high power for 1 minute.
4. While the microwave oven is operating, measure the line voltage at the power source. See “Measure Voltage” illustration.
5. Verify the voltage is constant during microwave oven operation. If voltage drops below 108V, contact a qualified electrician to check your electrical supply.
6. Make note of the voltage while the microwave oven is running and proceed to the output test.

#### Output Test

1. Fill the measuring cup with 2 cups (500 mL) of 70°F (21°C) tap water.
2. Stir the water with the thermometer to ensure uniform temperature. Add warm or cool water to bring the water to the correct temperature.
3. Place the measuring cup in the center of the microwave oven cavity.
4. Operate the microwave oven on high power for 1 minute.
5. Remove the measuring cup and stir the water with the thermometer for about 20 seconds.
6. Record the temperature of the water.
7. Refer to the model serial tag on the microwave oven to acquire wattage output rating of the microwave oven.

### Measure Voltage



- A. House power supply wall outlet
- B. Voltmeter/ohmmeter test leads
- C. Microwave oven plug

8. Using the following chart, determine if the output of the microwave oven is within the range listed based on the line voltage and wattage rating of the microwave oven.

Water Temperature for Line Voltage and Wattage Rating			
Voltage	700W	1000W	1200W
120V	96°F to 102°F (36°C to 39°C)	110°F to 116°F (43°C to 47°C)	124°F to 130°F (51°C to 54°C)
108V	91°F to 97°F (33°C to 36°C)	101°F to 107°F (38°C to 42°C)	111°F to 117°F (44°C to 47°C)

## COMPONENT TESTS

### IMPORTANT:


- Unplug microwave oven or disconnect power.
- Discharge the high-voltage capacitor and remove the lead wires from the primary winding of the high-voltage transformer before conducting any of the following tests.
- Remove the lead wires from the related component before conducting any of the following tests.
- All operational checks using microwave energy must be done with the microwave oven loaded with a minimum of 8 oz (250 mL) of water in a microwave-safe container.
- Conduct a microwave energy test after performing any tests or repairs to the microwave oven.
- Check that all wire leads are in the correct positions before operating the microwave oven.
- Grasp wire connectors when removing the wire leads from microwave oven parts.
- All testing must be done with an ohmmeter having a sensitivity of 20,000 ohms per volt DC or greater and powered by at least a 9-volt battery.

Components	Test/Results	Components	Test/Results
<b>H.V. Transformer</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Primary winding: Less than 0.5 ohm (approximate)</li> <li>■ Secondary winding: 80 ohms (approximate)</li> <li>■ Filament winding: 0 ohms</li> <li>■ Primary winding to grounding: Normal: Infinite</li> <li>■ Filament winding to grounding: Normal: Infinite</li> </ul> </li> </ol>	<b>Magnetron</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Filament terminal: Normal: Less than 1 ohm</li> <li>■ Filament to chassis: Normal: Infinite</li> </ul> </li> </ol>

# FOR SERVICE TECHNICIAN'S USE ONLY

Components	Test/Results	Components	Test/Results
<b>H.V. Capacitor</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Terminal to terminal: Normal: Momentarily indicates several ohms, gradually returns to Infinite</li> <li>■ Terminal to case: Normal: Infinite</li> </ul> </li> </ol>	<b>Hood Exhaust Fan Motor</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ High Speed—Normal: Red (R) and Blue (BU) wires: 100 to 200 ohms (approximate); Blue (BU) and Black (BK) wires: 40 to 100 ohms (approximate)</li> <li>■ Low Speed—Normal: Red (R) and Blue (BU) wires: 100 to 200 ohms (approximate); Blue (BU) and White (W) wires: 80 to 150 ohms (approximate)</li> </ul> </li> </ol>
<b>H.V. Diode</b>	<p><b>NOTE:</b> Some inexpensive meters may indicate infinite resistance in both directions.</p> <ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Forward: Normal: Continuity</li> <li>■ Reverse: Normal: Infinite</li> </ul> </li> </ol>	<b>HF NTC Thermistor</b>	<ol style="list-style-type: none"> <li>1. If “NTC SHORT, CALL FOR SERVICE” or “NTC OPEN, CALL FOR SERVICE” scrolls on display, unplug microwave oven or disconnect power.</li> <li>2. Measure HF NTC thermistor: <ul style="list-style-type: none"> <li>■ Normal: 10k ohms +/-5% at 77°F (25°C)</li> </ul> </li> </ol>
<b>Turntable Motor</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Normal: 2.7k to 3.8k ohms (approximate)</li> </ul> </li> </ol>	<b>AC Line Filter Board</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Normal: L-IN to L-OUT (coil): Less than 1 ohm; N-IN to N-OUT (coil): Less than 1 ohm</li> </ul> </li> </ol>
<b>Motor Capacitor</b>	<ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure resistance: <ul style="list-style-type: none"> <li>■ Normal: Momentarily 0 ohms, then goes to Infinite</li> </ul> </li> </ol>	<b>Thermostats</b>	<p><b>NOTE:</b> Refer to “Parts Layout” for opening and closing temperatures.</p> <ol style="list-style-type: none"> <li>1. Unplug microwave oven or disconnect power.</li> <li>2. Remove wire leads.</li> <li>3. Measure continuity: <ul style="list-style-type: none"> <li>■ Normal: Continuity</li> </ul> </li> </ol>

## SCHEMATIC DIAGRAM



- Dwg. No.: MU-14S-T (rev. B)  
Condition: Door Open.
- Symbol Notes:  
BK — Wire Color - Black  
EP1-1 — Pin No. -1  
Connector Name
- HL: Hood (Cooktop) Light  
CXL: Cavity Light  
HF: Hood Fan Motor  
TT: Turntable Motor
- BK: Black  
BU: Blue  
RD: Red  
WH: White  
BR: Brown
- OR: Orange  
YL: Yellow  
GN: Green  
GY: Gray  
YL/GN: Yellow/Green
- ACU: Printed Circuit Board Assembly  
EP1\*EP2\*/P4/P6: Connectors  
\*There are purposely empty terminals between each of the numbered terminals on this connector.